



**DIMENSIONS**

LEAKAGE DISTANCE	1,387 mm
DRY ARCING DISTANCE	550 mm
SHEDS Q'TY	8 PCS

**MECHANICAL VALUES**

SPECIFIED CANTILEVER LOAD	11 kN
ROUTINE CANTILEVER LOAD	5.5 kN

**ELECTRICAL VALUES**

Low-Freq. FLASHOVER-DRY	230 kV
Low-Freq. FLASHOVER-WET	200 kV
IMPULSE FLASHOVER-POS	380 kV
IMPULSE FLASHOVER-NEG	470 kV

**PACKING INFORMATION**

NET WEIGHT EACH	14 kg
PACKED WEIGHT EACH	14.4 kg
NO. IN STANDARD PACKAGE	3 PCS

**NOTE:**

1. END FITTINGS ARE MADE FROM SPHEROIDAL GRAPHITE CAST IRON.
2. FIBERGLASS ROD IS MADE FROM EPOXY RESIN.
3. CLAMP AND STUD BASE DIMENSIONS ARE IN ACCORDANCE WITH ANSI C29.7
4. THE DIA. OF FRP ROD IS 45mm SOLID.
5. BASE AND INSULATOR ASSEMBLED WITH M20 BOLT AND WASHER.

<small>THESE DRAWINGS AND SPECIFICATIONS, AND THE DATA CONTAINED THEREIN, ARE THE EXCLUSIVE PROPERTY OF DTR CORPORATION. THESE DRAWINGS ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT, WITHOUT THE PRIOR WRITTEN PERMISSION OF DTR CORPORATION, BE REPRODUCED, COPIED, OR USED FOR ANY PURPOSE WHATSOEVER, EXCEPT THE MANUFACTURE OF ARTICLES FOR DTR CORPORATION.</small>	DIMENSIONAL TOLERANCES UNLESS OTHERWISE NOTED X ±0.1 XX ±0.02 XXX ±0.010 ANGLES ±1°	Designed by C.H.PARK	Date 09/30/09	Part Number DTR-LPV69SK-NZI	Scale N/A
					<b>69kV LINE POST INSULATOR VERTICAL</b>
Filepath			Units mm	Sheet 1/1	