

"A"

50

322

284

475

103

40.5

20.25

Ø121

Ø91

Ø55

1

4

10

161

M12

57

M10

114

82

32

114 ~ 140

68 ~ 102

18 P9X3=27

Cu CONDUCTORS OF REAL CROSS SECTION : 16sqmm-50sqmm

Cu CONDUCTORS OF REAL CROSS SECTION : 16sqmm-25sqmm

2

3

6

7

9

8

10

11

5

12

< DETAIL "A" >

REPLACEABLE

ORIGINAL DWG

COMMON TO DECIMAL

REPLACEABLE MATERIAL	NO	PART NAME		EA	MATERIAL	DWG NO
PART LISTS						
COMMON TOLERANCE DECIMAL ANGLE FRACTION	DATE 03/05/2026 APP DIVISION R&D Team			 TITLE Polymer Surge Arrester for Distribution (24kV, 10kA, Class 1 Surge Arrester)		
MATERIAL	CHK BY KC. PARK	APP BY DH.YOO				
HEAT TREATMENT	DWG BY BJ. KIM			SIZE DWG NO CA 24/10.1D		
	DWG DIVISION R&D Team					
CORROSION PROTECTION	SCALE 1:1	UNIT mm	WEIGHT	A3 SHEET 1 OF 1		