



REMARK :

1. Ferrous parts shall hot dip galvanized except the stainless steel
2. The coupling size of tongue and clevis comply for IEC –120 size 16C
3. Weight : 4.0 kgs
4. Colour of insulator : trans-parent light green
5. The bounding surface between the tongue and cement shall painted With bituminous coating
6. Creepage distance : 320mm
7. All dimension is in mm .
8. Spacing : 146mm
9. Mark in the insulator : name , trade mark, year, 70kN

| ITEM | Description of the goods | Quantity | Material | Type LXY-70C IEC Class U70C Glass Disc Insulator | | |
|------|--------------------------|----------|---|--|--|----------|
| 1 | Coupling Pin | 1 | Forged Steel , Hot Dip Galvanized | | | |
| 2 | Locking Key | 1 | Stainless Steel | | | |
| 3 | Insulator Cap | 1 | Malleable Cast Iron ,Hot Dip Galvanized | | | CODE NO. |
| 4 | Portland Cement | | No. 525 | | | 132217 |
| 5 | Washer | 1 | Asphalt Felt | Approved By : | | Date : |
| 6 | Insulator Pin | 1 | Forged Steel , Hot Dip Galvanized | Designed By : | | Date: |
| 7 | Glass body | 1 | Toughened Glass | Checked By : | | Date: |
| 8 | Washer | 1 | Plastic | Technology By : | | Date: |
| | | | | | | |